

NIECO CLOSE SCREW GROMMET






Insertion Video

Application

Commonly used on back door of vehicles

Features

High holding strength after attachment Fixed firmly Nut function with single-side operation Flange can function as spacer



Part No.	Туре	Hole Shape	Hole Size	Thickness	Screw Size	A	В	С	Material 1	Water Seal
2568	Closed Type	Square	□7.0	0.6~0.9	5	0.9	15.1	ф12.0	PA6	Off
3V67	Closed Type	Square	□8.0	0.7	5	1.5	11.4	□15.0	PA6	On
2F36	Closed Type	Square	□8.5	0.65~1.0	5	1.3	17	ф16.0	PA6	On
2147	Closed Type	Square	□8.5, 9.0	0.7~0.8	6	1	17.7	ф20.0	PA6	Off
1W7K	Closed Type	Square	□9.0	0.65~1.4	6	1.5	16.5	ф18.0	PA6	On
1Z64	Closed Type	Square	□9.0	2.75~4.75	6	1	17.7	ф20.0	PA6	Off
1A36	Closed Type	Square	□9.0	3.5~5.0	6	1	16.5	ф16.0	PA6 +PA66	Off
OU2R	Closed Type	Square	□10.0	0.65~1.6	6	1.5	15	ф20.0	PA6	On
1H6X	Closed Type	Square	□7.0 7.0	0.6~1.2	5	0.9	15.1	ф12.0	PA6	On
28E0	Closed Type	Square	□7.0	0.65	4	1.2	15	□10.0	PA6	Off
2V8H	Closed Type	Square	□7.0	0.7	5	1.2	9.3	ф12.0	PA6	On
2X7E	Closed Type	Square	□7.0 =8.0	0.7 0.8	5 5	1.2	15	ф12.0	PA6	On
10U2	Closed Type	Square	□8.0		6	1.1 1.3	15.9 16.7	□12.0	PA6 PA6	On Off
4T46 0W8D	Closed Type Closed Type	Square	□8.25~8.8 □8.5	1.3~2.0 0.6~1.2	5	1.3	14	φ18.0 □14.0	PA6	Off
3B14	Closed Type	Square Square	□8.5	0.8~1.2	6	1.5	14.5	ф16.0	Other	On
1Z05	Closed Type	Square	□8.5	0.7~0.75	6	1.3	15.5	φ15.0 □15.0	PA6	Off
496N	Closed Type	Square	□8.5	0.7~1.2	5	4	15.5	□13.0	PA6	On
5464	Closed Type	Square	□8.5	0.75	5	1	15	□13.0 □13.0	PA6	Off
4896	Closed Type	Square	□8.5	0.8	6	1.3	15.5	□13.0	PA6	Off
297	Closed Type	Square	□8.5	0.8~1.0	6	1.3	17.7	ф18.0	PA6	On
2200	Closed Type	Square	□8.5	0.8~1.0	5	1.3	16.7	ф16.0	PA6	Off
2F76	Closed Type	Square	□8.5	0.8~1.0	6	1.3	17.7	ф18.0	PA6	Off
21G0	Closed Type	Square	□8.5	0.8~1.2	6	5.5	14.5	ф18.0	Other	Off
21B5	Closed Type	Square	□8.5, 9.0	0.7~0.8	6	1	23	ф20.0	PA6	Off
244B	Closed Type	Square	□ 8.5 , 9.0	0.7~0.8	6	1	17.7	ф20.0	PA6	Off
358B	Closed Type	Square	□8.5, 9.0	0.7~0.8	6	1	23	ф20.0	Other	Off
3D92	Closed Type	Square	□9.0	0.6~2.1	5	1.3	16.2	ф16.0	PA6	On
090A	Closed Type	Square	□9.0	0.65	6	2	14.5	□14.0	PA6	Off
3P1N	Closed Type	Square	□9.0	0.65~1.2	6	4.8	16.3	ф18.0	PA6	On
25E9	Closed Type	Square	□9.0	0.65~1.4	6	1.3	16.7	ф18.0	PA6	Off
4F22	Closed Type	Square	□9.0	0.65~2.0	6	5.5	14.5	ф18.0	Other	Off
039J	Closed Type	Square	□9.0	0.65~2.0	6	5.5	14.5	ф18.0	Other	Off
OP2X	Closed Type	Square	□9.0	0.75~1.2	6	5.5	14.5	ф18.0	Other	On
4643	Closed Type	Square	□9.0	0.8~1.0	6	1.3	16.7	ф18.0	PA6	Off
353V	Closed Type	Square	□9.0	0.9~3.8	6	1.2	18.8	ф16.0	PA6	Off
4644	Closed Type	Square	□9.0	2.8	6	1	19	φ16.0	PA6	Off
31T0	Closed Type	Square	□9.0	2.8~4.5	6	1	22.7	ф20.0	PA6	Off
4B6U	Closed Type	Square	□10.0	0.7~0.75	6	3.35	16.5	ф18.5	Other	On
2464	Closed Type	Square	□10.0	0.7~0.9	6	2	18	ф20.0	Other	Off
2V47	Closed Type	Square	□10.0	0.7~1.0	6	1.5	15	ф20.0	PA6	On
30M0	Closed Type	Square	□10.0	0.7~1.0	6	5	16.5	ф19.0	Other	Off
3H0A	Closed Type	Square	□10.0	0.7~1.0	6	3.05	16.75	ф14.0	Other	On
2J33	Closed Type	Square	□10.0	0.8	5	8.0	11	ф16.0	PA6	Off